

## Diamond stone cutter for wet cuts, mitre cuts up to 45 °, with GFCI circuit breaker

### CS 60 WET

Order number 374.016



#### Technical attributes

Power input	1400 watt
Power output	840 watt
No load speed	6200 rpm
Diamond cutting disc Ø / arbor (inside Ø)	170 / 22,2 mm
Cutting depth / with guide rail	60 / 54 mm
Mitre cuttings	0-45 °
Depth of cut - mitre cut	5-44 mm
Depth of cut - mitre cut with guide rail	0-38 mm
Cable length	4,0 m
Size (W x L x H)	360 x 280 x 170 mm
Weight	4,5 kg

#### Diamond stone cutter for wet cuts, mitre cuts up to 45 °, with GFCI circuit breaker

- + High-performance motor: extra powerful for stone cutting and joint milling
- + Continuous cut depth setting from 0-60 mm, with rail guide up to 54 mm. In the mitre cut from 0-44 mm, with guide rail up to 38 mm
- + Continuous angle adjustment for mitre cuts from 0-45°
- + Cut marking at the base plate from 0°/30°/45° for rapid orientation
- + High-quality magnesium die-castings for protective cover and base plates
- + Motor protection made of rubber prevents the direct intake of spray water
- + Water supply: for an effective cooling of the diamond blade
- + Quick-fit brass coupling: for 1/2" water hose
- + GFCI operator protector circuit breaker: integrated in cord
- + Ideal for: Inserting water grooves in window sills or steps, work tops, facade slabs, terrazzo slabs in garden design & landscaping, joint renovation in the floor
- + Spindle lock

#### Standard equipment

1 diamond cutting disc with segmented cutting edge	347.515
1 wrench for saw blade change	359.343
1 parallel guide fence	350.613
1 carrying case L-BOXX® 238	414.093
1 case insert	436.771